



QUALITY METERING PRODUCTS

MULTI CHANNELS ENERGY POWERMETER

Up to 12 sets of three phase energy meters or
Up to 36 single phase energy meters or
Up to 36 Digital Inputs.
Up to 4 months of energy data logging.
Electrical variables displays.
1,600 samples per cycle.
Accuracy 0.2 %.
Ethernet (TCP/IP) and RS-485 ports.
Modbus and BACnet protocols (RTU/MSTP/IP).
Web browser capability.
Simple operated menus.
High resolution color display (320x240 pixels).
Simple installation – DIN Rail mounted.
Multilingual support.

Technical Specifications


Power Requirements : 90 - 250 VAC
: 110 - 280 VDC
: 60/50 Hz
: 11VA
Dimensions (H x W x D) : 110 x 300 x 60 mm
Shipping Weight : 1,250 gr.
Working Conditions : -20 – 70°C
: 0 - 95 RH%

Measurement Range:

Voltage : 0 - 550 VAC
Voltage (with transformer) : up to 9999999999 MV
Current (with transformer) : up to 9999999999 MA
Maximum Input Voltage : 1000V
Maximum Input Current : 6A
Supported Current Sensors : 0.333 V / 1 Amp /
5 Amp / 63 Amp / 0.1 Amp

Standard Approvals:

EN62052-11, EN62053-22, EN62053-23, CE, UL61010,
EN61000-3-2, EN61000-3-3, BTL



Quality Metering Products
24011 Lemmon Arbor Dr
Spring, TX 77389
Tel (281) 4194674
Fax (281) 857645
www.qualitymetering.net